AFCONA - 3085

Chemical Composition

Organic modified polyether polysiloxane.

Product general description

Slip and leveling agent hydroxyl functional terminated.

Product Properties:

AFCONA-3085 is a polysiloxane based polymer with di-hydroxyl functional groups terminated at both end. This enables AFCONA – 3085 to cross-link in polyurethane system as well as in baking paints.

With the cross-linking properties AFCONA – 3085 specially is designed to give permanent slip to polyurethane coatings and baking paints.

AFCONA – 3085 is very compatible with most systems. Therefore, it could stabilize foam. Thus, in foam sensitive systems a suitable defoamer needs to be combined. For normal conventional pressure spray, additional defoamers are not needed.

AFCONA-3085 can be used in all solvent based as well as all water based systems.

Product Specification

Non-volatile matter	50 - 54% (120°C,0.5h)
Solvent	2-Butoxyethanol
Density	$0.96 - 0.98 \text{ g/cm}^3 (20^{\circ}\text{C})$
The refractive index	1.425 – 1.435 (25°C)
Flash point	32°C
Appearance	Transparent to slight yellowish liquid (25°C)

Addition and dosage

0.1- 1.0% on total formulation. In general under normal conditions, the dosage is 0.2 - 0.5%based on total formulation. To prevent hand marking in PU wood coatings, the dosage needed is 1 - 3% on total formulation.

Incorporation

AFCONA-3085 can be added at any stage during the production process. If added during the dispersion process, it speeds up wetting.

<u>Storage</u>

AFCONA-3085 should be stored in a cool dry place. When kept in an original unopened container, it will keep up to 5 years from the date of manufacture. The expiry date is indicated on the container.

<u>Packaging</u>

25kg and 190 kg non-returnable containers

AFCONA ADDITIVES Web Site : www.afcona.com

This information and all further technical advice are based on our present knowledge and experience. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, sepecially patent rights. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used. We reserve the right to make any changes according to science and technological progress or further developments.