AFCONA - 2028



Chemical Composition

Silicone containing defoaming polymer.

Product general description

A moderate defoamer and easy to incorporate.

Product properties

AFCONA-2028 prevents formation of foam and blisters during the manufacturing and application of solvent-based wood finishes.

AFCONA-2028 is particularly suitable as a defoamer for curtain coatings as well as during production. When foam causes a problem during packaging, AFCONA-2028 can be added slowly, while stirring to speed up the bubble breaking process. In this case, AFCONA-2028 is more user-friendly and easier to handle than AFCONA-2022, because it is less sensitive to crater formation and other well-known defoamer side effects.

AFCONA-2028 can be used in:

- 1) polyurethane coatings for wood, plastic and car refinish.
- 2) unsaturated polyester systems.
- 3) acid curing coatings for wood.
- 4) NC lacquers for wood coatings and general industrial.

Product Specification

Solvent Xylene/ Ethyl Acetate/

Methoxy Propyl Acetate/

Butyl Acetate

Density at 20° C 0.88 - 0.90g /cm³

The refractive index 1.475 - 1.485

Flash point 36°C

Appearance Clear to slightly yellow liquid

Addition and dosage

0.1- 1.0% on total formulation. In general under normal conditions, the dosage is 0.20-0.40% based on total formulation.

Incorporation

AFCONA-2028 can be incorporated prior to processing. If added subsequently, good dispersion must be ensured.

Storage

AFCONA-2028 should be stored in a cool and dry place. When kept in an original unopened container, it will keep up for 5 years from the date of manufacture. The expiry date is indicated on the container.

Packaing

20kg and 170kg non-returnable containers